

Philips
PAL coax cable

1,5 m

> 75 dB Ferrite core

SWV2824W



Ensure a reliable connection

with this PAL type coaxial cable

Depend on this cable to provide you with a reliable audio/video connection between components.

Enjoy good picture quality

- Gold-plated connectors for better conductivity

Enjoy good audio quality

- High purity copper conductor for reliable signal transfer

Protects against signal loss

- Bare copper shielding

Easy installation

- Non-slip ergonomic grip for easy use

Enjoy extended durability

- Molded plug for secure connections
- Flexible PVC jacket
- Rubber strain relief

PHILIPS

sense and simplicity

PAL coax cable
1,5 m > 75 dB Ferrite core

Specifications

Packaging dimensions

- **Packaging dimensions (W x H x D):**
9.4 x 23.6 x 2.5 cm
- **Nett weight:** 0.101 kg
- **Gross weight:** 0.120 kg
- **Tare weight:** 0.019 kg
- **EAN:** 87 12581 38037 3
- **Number of products included:** 1
- **Packaging type:** Blister

Outer Carton

- **Outer carton (L x W x H):** 33.0 x 25.4 x 12.2 cm
- **Nett weight:** 1.212 kg

- **Gross weight:** 1.790 kg
- **Tare weight:** 0.578 kg
- **EAN:** 87 12581 38039 7
- **Number of consumer packagings:** 12

Inner Carton

- **Inner carton (L x W x H):** 24.4 x 10.4 x 10.2 cm
- **Nett weight:** 0.404 kg
- **Gross weight:** 0.540 kg
- **Tare weight:** 0.136 kg
- **EAN:** 87 12581 38038 0
- **Number of consumer packagings:** 4

SWV2824W/I0

Product highlights

Bare copper shielding

Bare copper shielding protects against signal loss.

Easy grip

This non-slip grip makes connecting your components easy and ergonomically comfortable.

Flexible PVC Jacket

Flexible PVC jacket provided protection to the delicate core of the cable. It also offers extended durability and ease of installation.

Gold-plated connectors

Gold-plated connectors provide better conductivity by lowering contact resistance. They also prevent connector deterioration through oxidation.

High purity copper

This copper conductor provides high accuracy in signal transfer with minimal resistance.

Molded plug

Molded plugs ensure secure connections between components and offer extended durability.

Rubber strain relief

Rubber strain relief provides a secure, yet flexible juncture between the cable and the plug.



Issue date 2008-09-25

Version: 1.0.9

12 NC: 8670 000 35465
EAN: 87 12581 38037 3

© 2008 Koninklijke Philips Electronics N.V.
All Rights reserved.

Specifications are subject to change without notice.
Trademarks are the property of Koninklijke Philips
Electronics N.V. or their respective owners.

www.philips.com